Material Safety Data Sheet

Fluorescent pigment Blue

Product Code: PS-FL0198

Department: fluorescent pigments

C.A.S.: 26160-89-4, various dyes and pigments



Section: 1 Identification

Product Name: Fluorescent pigment Blue

Recommended Uses: thermoset fluorescent pigment use in inks, paints and coatings.

Section: 2 Hazard Identification

OTHER HAZARDS NOT OTHERWISE CLASSIFIED UNDER GHS - OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION:

The resin in this product series contains less than 0.1% residual / free formaldehyde. Heat / fire conditions may cause the release of formaldehyde gas in excess of the OSHA action level of 0.5 ppm, pel of 0.75 ppm twa, and 15 minutes stel of 2 ppm twa. Formaldehyde is "carcinogenic to humans" according to iarc and an irritant.

HGS Label Elements

Signal Word

GHS Classification

Not regulated under SGH

Hazard Statements

No known significant effects or critical hazards.

Precautionary Statements

Prevention :none assigned under ghs Response :none assigned under ghs Storage :none assigned under ghs Disposal :none assigned under ghs

Section: 3 Composition / Information on Ingredients

CHEMICAL COMPOSITION:	COMPONENTS:	CAS NO.	%
	All colors are colored		
	benzoguanamine-formaldehyde resin primary	26160-89-4	89-100
	PS-FL0188, PS-FL0192, PS-FL0194		
	Contain C.I. Basic red 1	989-38-8	1-1.5
	(This dye is reportable under sara title iii, section	on 313 rules at 1.0% concentration)	
	PS-FL0194 contains C.I. basic violet 10	81-88-9	5-10
	Other various dves / pigments	not classified	0.1-10

Section: 4 First-Aid Measures

FIRST AID/ RESPONSE FIRST AID RESPONDERS SHOULD WEAR PERSONAL PROTECTIVE EQUPMENT

SKIN: if on skin promptly wash off with soap & water. Remove contaminated clothing. Get medical

advice/attention if irritation occurs. Wash contaminated clothing before reuse.

EYES: if in eyes:rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention if irritation occurs.

INHALATION: if inhaled:remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical advice / attention if any adverse symptoms occur.

INGESTION: if swallowed:rinse mouth with water, then drink water to dilute. Induce vomiting only under the direction

of medical personnel. Never give anything by mouth if the victim is unconscious. Get medical attention

if large quantity is ingested or if you feel unwell.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

Inhalation of dust or processing fumes may cause respiratory irritation, mucous secretion or inflammation. Dust contact with skin or eyes may cause slight irritation. In some individuals prone to sensitivities, prolonged or repeated overexposure may cause dermatitis or respiratory sensitization.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY Call a poison center/doctor/physician if you feel unwell.

Section: 5 Fire-Fighting Measures

Suitable extinguishing media: water: (x-as spray/fog) Foam: (x) co2: (x) dry chemical: (x)

Do not use high pressure water jet.

Specific hazards in case of fire: heat/ fire conditions will emit highly toxic, irritating and carcinogenic gases / fumes upon

burning. Treat as a flammable dust in the finely divided and suspended state. Dust cloud

formation from pigment powder may create a dust cloud explosion hazard.

Special protective equipment &

Precaution for fire fighters: in case of fire involving this material, do not enter the fire area without proper protective

equipment including self-contained breathing apparatus.

Section: 6 Accidental Release Measures

Personal precautions: wear full protective equipment (see section 8). Keep unprotected personnel out

of the area. Keep away from high heat and all sources of ignition. Control pigment powder dust cloud formation to prevent possible dust/air explosion

hazard.

Environmental precautions: avoid release to sewers and the environment. Dispose of properly via licensed

chemical waste hauler.

Methods and material for containment and clean up: vacuum or scoop into a properly labelled container and seal. Avoid generating

dust.

Section: 7 Handling And Storage

precautions for safe handling: avoid breathing dust and contact with skin & eyes. wear full protective

equipment (see section 8). use with adequate ventilation. avoid scattering into the air. avoid release to the sewer system. employ good housekeeping techniques to control dust build-up on equipment and work area. avoid dusting in areas of flame, sparks, & static buildup. properly ground processing / handling equipment. wash thoroughly after handling.

conditions for safe storage, including incompatibilities: store in a sealed container in a cool, dry area.

Section: 8 Exposure Control/Personal Protection

Exposure limits:

U.S. OSHA PEL: 0.5ppm action level; 0.75 ppm twa pel; 0.2 ppm stel for formaldehyde (as free

formaldehyde)

U.S. ACGIH TLV: 0.3 ppm twa ceiling limit for formaldehyde (as free formaldehyde) If processing

conditions have the potential to off-gas formaldehyde, follow the OSHA formaldehyde

standard at 40cfr1910.1048

use local / mechanical exhaust to maintain air concentrations below occupational Appropriate engineering controls:

exposure standards (see above)

Personal protective equipment:

Respiratory protection: use NIOSH approved respirator suitable to meet permissible exposure limit. See U.S.

OSHA respiratory standard (20 cfr 1910.134).

use chemical resistant gloves (rubber, PVC) Hand protection:

Eye protection: safety goggles or glasses with side shields or full face shield; access to an eyewash

fountain

Other protective equipment: lab coat; coveralls to protect skin; access to a safety drench shower.

Section: 9 Physical and Chemical Properties

Appearance: **Bright Colored Powder**

Flammable limits:

LEL & UEL: (N/A)

Odor:

slight aldehyde odor

Possible vapor pressure (mm hg): N/A Odor threshold: N/A Vapor density (air=1): N/A Ph (10% in water): 4-6 Relative density/specific gravity: 1.3

Melting point / freezing point (°c): decomposes at 150 (302°f)

Solubility in water (@20 °c): insoluble Boiling point (°c): N/A

Partition coefficient (n-octanol/water): no data available

Flash point (°f): N/A Auto ignition temp. (°c): N/A Evaporation rate: N/A

Decomposition temp.: 150 (302ºF) no data available Flammability:

Viscosity: N/A

Section: 10 Stability And Reactivity

Chemical stability: stable when stored in sealed package under recommended storage conditions

Possibility of hazardous reactions: hazardous polymerization will not occur

Conditions to avoid: contact with incompatibles; high heat (>150 °c or 300 °f); dust in vicinity of ignition sources,

electrical or spark generating equipment

Incompatible materials: strong oxidizing agents

Hazardous decomposition products: toxic fumes, smoke, oxides of carbon / nitrogen / sulfur and formaldehyde [irritating &

carcinogenic]

Section: 11 Toxicological Information

Potential health effects:

Routes of exposure: skin, eyes, inhalation, ingestion

Skin, eyes, and inhalation: inhalation of dust or processing fumes may cause respiratory irritation, mucous secretion.

and inflammation. Dust contact with skin or eyes may cause slight irritation. .

Ingestion: this route of exposure is not likely. No known effects.

Chronic: in some individuals prone to sensitivities, prolonged or repeated overexposure may

cause dermatitis or respiratory sensitization

Acute toxicity: expected to be oral (rat) LD50:> 2000mg/kg; dermal(rat) LD50:> 2000mg/kg - based on

testing of similar products

Skin corrosion / irritation:

Serious eye damage / irritation:

Respiratory or skin sensitization:

Germ cell mutagenicity:

no test data available
no test data available
no test data available

Carcinogenicity:

U.S. listed carcinogen: none () OSHA (*) NTP (*) IARC (*) other (*)

*if formaldehyde is off-gassed: formaldehyde, CAS# 50-00-0 is listed as OSHA-ca: carcinogen defined with no further categorization NTP-k: known to be a human carcinogen; IARC-1: carcinogenic to humans

C.I. basic red 1 (rhodamine 6g based), CAS# 989-38-8 and C.I. basic violet 10 (Rhodamine b based) CAS#81-88-9: IACR-3: unclassifiable as to carcinogenicity in humans (see section 3 for colors containing these two dyes)

Reproductive toxicity: no test data available

Specific target organ toxicity: none known
Aspiration hazard: no data available

Interactive effects: may aggravate colds, respiratory allergies, skin disorders

Section: 12 Ecological Information

Ecotoxicity: avoid release to the environment as this product series has not been tested

Toxicity - aquatic:

Toxicity to daphnia:

Toxicity - terrestrial:

Persistence & degradability:

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

no test data available
no test data available
no test data available
no test data available

Section: 13 Disposal Considerations

Disposal methods:

Dispose of contents / container in accordance with local, regional, national, international regulations. Dispose of in sealed containers, using a licensed chemical waste hauler.

Section: 14 Transport Information

By road or rail - U.S. d.o.t. regulated: yes () no (x) Required: (N/A) If regulated, UN proper shipping name: N/A hazard class: ()
UN identification no.: () packing group: () label required: ()

U.S. marine pollutant: yes () no (x) severe U.S. marine pollutant:yes () no (x)

Emergency response guide no.: ()

Inland B/L:

By sea - IMDG regulated: yes() no(x) stowage category: N/A By air - IATA regulated: yes() no(x) pkg instruction no.: N/A

Special precautions: read SDS before handling

Section: 15 Regulatory Information

U.S. tsca: We certify that all components of this product are registered under the regulations of the

toxic substances control act.

U.S. sara title iii, sect. 313: listed (*) not listed ()

*only PS-FL0188, PS-FL0192, PS-FL0194 are listed for C.I. basic red 1, CAS# 989-38-8, at 1-1.5% (see section 3)

U.S. rcra hazardous waste : no (x) yes ()rcra # :()
U.S. cercla : no (x) yes ()required (**)

U.S. california proposition 65 listed : yes (x*) no ()

*this product series contains a chemical known to the state of california to cause cancer:

formaldehyde, cas# 50-00-0, at less than 0.1%.

HMIS: health (1) flammability (1) reactivity (0)

Section: 16 Other Information

reference manufacturer's material safety data sheet

prepared by kama pigments

abbreviations / acronyms: N/A=not applicable; LEL=lower explosion limit; UEL=upper explosion limit; PEL=permissible exposure

limit; STEL=short term exposure limit; TLV=threshold limit value; TWA=time weighted average over 8 hour workday; LD50 or LC50=lethal dose or lethal concentration that kills 50% of dosed group; mg=milligram; g=gram; kg=kilogram; ppm=parts per million; m=meter; LOAEL=lowest observed

adverse effect level; C.I.=colour index.

Disclaimer:

Kama pigments, expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information, refer to a Product Specification Sheet and/or a Certificate of Analysis. These can be obtained from your local Kama pigments Sales Office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Kama pigments makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Kama pigments' control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.



Last revision: 2017-10-27